



YOUR DEALER

Euroengel
Professional mobile refrigeration

Euroengel srl
25128 Brescia - Italia
Via Ferrini 14
tel +390302005058
fax +390302007433
e-mail info@euroengel.it
www.euroengel.it

Refrigerant R134a - CFC free

Comply with:
2006/95/EC
2004/108/EC
93/43/EC (HACCP)

Versions, technical modifications
and delivery options reserved.



2010

Professional
Mobile
Refrigeration

	T0022/FDN	T0032/FDN	T0056/FDN	T0082/FDN	T0140/NDN T0140/FDN	T0330/NDN T0330/FDN	F0140/NDN F0140/FDN	F0330/NDN F0330/FDN
								
Tipo Type	Top Loader	Top Loader	Top Loader	Top Loader	Top Loader	Top Loader	Front Opening	Front Opening
Volume lt Volume lt	22	32	56	82	140	330	140	330
Dim. Est. mm Ext. Dim. mm	590x380x480	670x390x480	800x500x500	940x560x550	620x710x1000	1000x910x1020	1000x620x710	1020x1000x910
Dim. Int. mm Int. Dim. mm	290x230x350	360x250x350	450x330x350	540x370x360	410x510x620	610x660x810	620x410x510	810x610x660
Isolamento mm Insulation mm	65-70	65-70	70	80	80-100	100	80-100	100
Termostato Thermostat	Digital	Digital	Digital	Digital	Digital	Digital	Digital	Digital
Voltaggio V Voltage V	12-24 Vdc 100-240 Vac	12-24 Vdc 100-240 Vac	12-24 Vdc 100-240 Vac	12-24 Vdc 100-240 Vac	12-24 Vdc 100-240 Vac	12-24 Vdc 100-240 Vac	12-24 Vdc 100-240 Vac	12-24 Vdc 100-240 Vac
Peso Kg Weight Kg	17	19	26	29	40 45	90 95	40 40	90 90
Temperatura °C Temperature °C	>-24°C	>-24°C	>-24°C	>-24°C	>-10°C >-21°C	>+0°C >-21°C	>-10°C >-21°C	>+0°C >-21°C
Consumo Max A Max consump. A	9A (12V)	9A (12V)	9A (12V)	9A (12V)	9A (12V) 18A (12V)	9A (12V) 18A (12V)	9A (12V) 18A (12V)	9A (12V) 18A (12V)
Compressore Compressor	1xBD50F	1xBD50F	1xBD50F	1xBD50F	1xBD50F 2xBD50F	1xBD50F 2xBD50F	1xBD50F 1xBD80F	1xBD50F 1xBD80F
OPT su richiesta OPT on request	+40°C>24°C	+40°C>24°C	+40°C>24°C	+40°C>24°C	+40°C No >-10°C	+40°C No >+0°C	+30°C No >-10°C	+30°C No >+0°C

